

CCI LEAKGUARD™



ACRYLIC POLYMER FOR WATER PROOFING

PRODUCT:-	Single component, medium density, ready to use Acrylic Polymer for all water proof applications.
BENEFITS:-	Pre-packed & factory controlled product ensures excellent waterproofing characteristics, excellent adhesion, flexible layer, seals porosity and delivers water tightness.
PACKING:-	LEAKGUARD is a single component and available in 5 Ltr, 50 Ltr, & 200 Ltr packing.
USES:-	For water proofing applications on all concrete structures like Roof tops, basements, water tanks, sunken slabs, swimming pools, retaining walls, slope roofs etc. LEAKGUARD can also be used for coatings on asbestos sheets.
MIXING:-	LEAKGUARD is a single component specially designed for water proofing applications. Should preferably be mixed mechanically to ensure uniform mixing for better cohesive consistency. Mixing should be 1:1:3 ratio (1 Ltr of LEAKGUARD & 1 Ltr of Water and 3 kg Cement). Mix well for 2 to 3 minutes.
COVERAGE:-	LEAKGUARD after mixing at 1:1:3 ratio, coverage can be obtained from 50 to 60 sft, single coat, depending on the surface.
SHELF LIFE:-	Shelf Life of LEAKGUARD is 24 months. It should be stored in original sealed pack under shade in dry condition.
WATER CURING:	Water curing should be done 2 to 3 times in a day after 8 hours of application. Continuous water curing for 2 to 3 days, is an added advantage.

APPLICATION PROCEDURE:	<p>Surface preparation: Surface should be cleaned thoroughly by using wire brush and all loose particles, oil stains if any, dust, paint etc., should be removed and cleaned by sufficient quantity of water. Un-plastered, un-even surfaces or any cracks on the surface should be repaired to make it even for better bonding. Surface should be strong & sound.</p> <p>Application: The prepared surface should be sufficiently wet and water stagnation if any, should be removed. Then mixed LEAKGUARD to be applied uniformly by brush towards one direction maintaining proper hiding properties.</p>
QUALITY ASSURANCES:	<p>CCI INC., is an ISO 9001-2015 certified company and our products are in accordance with international standards.</p>

OUR PRODUCT RANGE
ADMIXTURES / WATER PROOFING
INDUSTRIAL FLOORING / ENGG. NON-SHRINK GROUTS
DOMESTIC FLOORING / SURFACE COATINGS/
CONCRETE REPAIRS



AN ISO 9001 - 2015 CERTIFIED COMPANY

CCI INC.

No. 41, CCI House, 7th B Jakkur Cross, Opp: St .John's School,
 Amruthahalli, BENGALURU- 560 092. Phone: +91 80 68997002
 Website: www.cciadditives.com / www.ccichemicals.com
 Email : info@ccichemicals.com sales@ccichemicals.com

Customer Support: +91 9481906617 / +91 80 68997002
 ISO 9001-2015 Certified Company
 CI 2016-17 - leakguard

The information given in this data sheet is based on both current development and many years of field experience. While every effort is made to ensure that the information is reliable, we can not accept responsibility of any work carried out with our products as we have no control over the application procedure adopted at site and site conditions. In view of continuous research and development in our laboratory, we advise customers ,in their own interest, to ensure that this data sheet has not been superseded by any other publication. Field services where provided, does not constitute supervisory responsibility. For additional information, CCI Inc local representative or customer care department may be contacted.

CCI INC