

CCI

CRACKSEALER-G™



SINGLE PART, CEMENTITIOUS, WATERPROOFED, CRACK FILLING COMPOUND

| | |
|---|--|
| <p>PRODUCT</p> | <p>Single pack, easy to use, high strength, water proofed, expanding characteristic, crack filling compound in grey colour.</p> |
| <p>BENEFITS</p> | <p>Better consistency, easy to use, excellent adhesion, water proofing & expanding characteristic, non-metallic and chloride free.</p> |
| <p>APPLICATION METHOD</p> | <p>The cracked area should be 'A' grooved. The surface should be widened (depth and width) to ensure proper repair and filling the cracks uniformly.</p> <p>All the debris and loose particles from the groove mouth be removed and pre-wet the surface with water. Pre-wetting the surface is a MUST. Apply by brush ADMIX SB LATEX on the wet surface of groove as a primer.</p> <p>Mix CRACKSEALER-G with water and ADMIX SB LATEX at 1:1 ratio. The addition of water (water/powder ratio), vary from place to place due to temperature and humidity. Therefore water should be used to mix CRACKSEALER-G till a homogenous or a semi-paste consistency is formed.</p> <p>Place the mixed CRACKSEALER-G deep into the grooved gap by a putty blade, allow it to get filled the area uniformly and finish it off.</p> |
| <p>IMPORTANT</p> <p>1.WATER CURING</p> | <p>CRACKSEALER-G has expanding characteristics to ensure perfect bond on both the sides of cracks and hence proper water curing is necessary. Water curing should be started after 2 hours of its application for smooth expansion and perfect bond. It is advised to cure the area with water 3 to 4 times a day for 2 days.</p> |
| <p>2. PRIMING IN LIEU OF WATER CURING</p> | <p>Immediately after CRACKSEALER-G application, apply one cover coat with ADMIX SB LATEX to enable CRACKSEALER G to set without evaporating water.</p> |

| | |
|---------------------------------|--|
| PACKING & SHELF LIFE | 5kg bags. Minimum 6 months from the date of manufacture if stored in original container under shade, unopened. |
| QUALITY ASSURANCES | CCI INC., is an ISO 9001-2015 certified company and our products are in accordance with international standards. |



CCI INC.

No. 41, CCI House, 7th B Jakkur Cross, Opp: St .John's School,
Amruthahalli, BENGALURU- 560 092. Phone: +91 80 68997002
Website: www.cciadditives.com / www.ccichemicals.com
Email : info@ccichemicals.com sales@ccichemicals.com

Customer Support: +91 9481906617 / +91 80 68997002

An ISO 9001-2015 Certified Company

CCI 2016-17 - cracksealer-g



AN ISO 9001 - 2015 CERTIFIED COMPANY

The information given in this data sheet is based on both current development and many years of field experience. While every effort is made to ensure that the information is reliable, we can not accept responsibility of any work carried out with our products as we have no control over the application procedure adopted at site and site conditions. In view of continuous research and development in our laboratory, we advise customers ,in their own interest, to ensure that this data sheet has not been superseded by any other publication. Field services where provided, does not constitute supervisory responsibility. For additional information, CCI Inc local representative or customer care department may be contacted.